

Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 9

SDS No.: 278985 V001.9

Revision: 10.02.2017 printing date: 04.05.2017 Replaces version from:

21.06.2016

blaugelb Acryl Dichtmasse all Colours

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

blaugelb Acryl Dichtmasse all Colours

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Joint sealant, acrylate

1.3. Details of the supplier of the safety data sheet

Meesenburg Großhandel KG

Westerallee 162

24941 Flensburg / DEUTSCHLAND

Phone: +49 (0)461 5808-0 Fax-no.: +49 (0)461 5808-1101

E-Mail: Zuständig für das Sicherheitsdatenblatt: sdb@chemiebuero.de

1.4. Emergency telephone number

Beratungsstelle +49 (0)89-19240 (24h) (deutsch und englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information Contains Isothiazolinone mixture 3:1 (CIT/MIT). May produce an allergic reaction.


Precautionary statement: P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.





MSDS-No.: 278985 blaugelb Acryl Dichtmasse all Colours Page 2 of 9 V001.9

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Joint sealants

Base substances of preparation:

Acrylate copolymer dispersion Mineral fillers

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-Reg No. | content | Classification |
|---------------------------------------|----------------------------|--------------|--------------------------------|
| Isothiazolinone mixture 3:1 (CIT/MIT) | | 1,5-< 15 PPM | Acute Tox. 2 |
| 55965-84-9 | | | H330 |
| | | | Acute Tox. 3 |
| | | | H301 |
| | | | Acute Tox. 2 |
| | | | H310 |
| | | | Skin Corr. 1B |
| | | | H314 |
| | | | Skin Sens. 1A |
| | | | H317 |
| | | | Aquatic Acute 1 |
| | | | H400 |
| | | | Aquatic Chronic 1 |
| | | | H410 |
| | | | M factor (Acute Aquat Tox): 10 |

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures



MSDS-No.: 278985 blaugelb Acryl Dichtmasse all Colours Page 3 of 9

V001.9

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure that workrooms are adequately ventilated.

Avoid skin and eye contact.

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container protected against moisture.

Store frost-free.

Store in a cool, dry place.

Temperatures between + 5 °C and + 30 °C

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Joint sealant, acrylate



MSDS-No.: 278985 blaugelb Acryl Dichtmasse all Colours Page 4 of 9 V001.9

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Germany

None

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Combination filter: ABEKP (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection:

Protective goggles

Skin protection:

Suitable protective clothing

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid pasty

varied, according to

coloration

Odor slightly, ammoniacal

Odour threshold No data available / Not applicable

pΗ No data available / Not applicable Initial boiling point No data available / Not applicable

Flash point Not applicable

Decomposition temperature No data available / Not applicable No data available / Not applicable Vapour pressure

Density 1,56 g/cm3

(20 °C (68 °F)) Bulk density No data available / Not applicable Viscosity No data available / Not applicable No data available / Not applicable Viscosity (kinematic) Explosive properties No data available / Not applicable

Solubility (qualitative) Insoluble

(23 °C (73.4 °F); Solvent: Water)

Solidification temperature No data available / Not applicable No data available / Not applicable Melting point Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable No data available / Not applicable Explosive limits



MSDS-No.: 278985 blaugelb Acryl Dichtmasse all Colours Page 5 of 9

V001.9

Partition coefficient: n-octanol/water

Evaporation rate

No data available / Not applicable

No data available / Not applicable

Vapor density

No data available / Not applicable

Oxidising properties

No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Sensitizing:

An allergic reaction cannot be excluded after repeated skin contact.

Acute oral toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|---------------------------------------|---------------|----------|----------------------|---------------|---------|---------------|
| Isothiazolinone mixture 3:1 (CIT/MIT) | LD50 | 53 mg/kg | oral | | rat | not specified |
| 55965-84-9 | | | | | | |

Acute inhalative toxicity:

| Hazardous components | Value | Value | Route of | Exposure | Species | Method |
|-------------------------|-------|------------|-------------|----------|---------|---------------------------|
| CAS-No. | type | | application | time | | |
| Isothiazolinone mixture | LC50 | 0,171 mg/l | aerosol | 4 h | rat | OECD Guideline 403 (Acute |
| 3:1 (CIT/MIT) | | | | | | Inhalation Toxicity) |
| 55965-84-9 | | | | | | |

Acute dermal toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|---------------------------------------|---------------|-------------|----------------------|---------------|---------|---|
| Isothiazolinone mixture 3:1 (CIT/MIT) | LD50 | 87,12 mg/kg | dermal | | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| 55965-84-9 | | | | | | - |

MSDS-No.: 278985 V001.9



Skin corrosion/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|------------------------------|-----------|---------------|---------|---------------|
| Isothiazolinone mixture | corrosive | | | not specified |
| 3:1 (CIT/MIT) | | | | |
| 55965-84-9 | | | | |

Respiratory or skin sensitization:

| Hazardous components CAS-No. | Result | Test type | Species | Method |
|------------------------------|-------------|-----------|------------|---------------|
| Isothiazolinone mixture | Sensitizing | | guinea pig | not specified |
| 3:1 (CIT/MIT) | | | | |
| 55965-84-9 | | | | |

SECTION 12: Ecological information

General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following. Do not empty into drains, soil or bodies of water.

12.1. Toxicity

| Hazardous components | Value | Value | Acute | Exposure | Species | Method |
|--|-------|-------------|--------------------|----------|--------------------------------|--|
| CAS-No. | type | | Toxicity Study | time | | |
| Isothiazolinone mixture 3:1 (CIT/MIT) | LC50 | 0,22 mg/l | Fish | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute |
| 55965-84-9 | NOEC | 0,098 mg/l | Fish | 28 d | Oncorhynchus mykiss | Toxicity Test) OECD Guideline |
| Isothiazolinone mixture 3:1 (CIT/MIT) | EC50 | 0,12 mg/l | Daphnia | 48 h | Daphnia magna | 210 (fish early lite stage toxicity test) OECD Guideline 202 (Daphnia sp. |
| 55965-84-9 | | | | | | Acute Immobilisation Test) |
| Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9 | EC50 | 0,048 mg/l | Algae | 72 h | Pseudokirchnerella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| | NOEC | 0,0012 mg/l | Algae | 72 h | Pseudokirchnerella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9 | EC10 | 0,59 mg/l | Bacteria | 16 h | | not specified |
| Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9 | NOEC | 0,0036 mg/l | chronic Daphnia | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

12.2. Persistence and degradability

| Hazardous components | Result | Route of | Degradability | Method |
|----------------------|--------|-------------|---------------|--------|
| CAS-No. | | application | | |



MSDS-No.: 278985 blaugelb Acryl Dichtmasse all Colours Page 7 of 9

V001.9

| | Isothiazolinone mixture 3:1 (CIT/MIT) | | aerobic | | OECD Guideline 302 B (Inherent biodegradability: Zahn- |
|---|---------------------------------------|-----------------------|---------|--------|--|
| | 55965-84-9 | | | | Wellens/EMPA Test) |
| ĺ | | readily biodegradable | | > 60 % | OECD Guideline 301 D (Ready |
| | | | | | Biodegradability: Closed Bottle |
| | | | | | Test) |

12.3. Bioaccumulative potential / 12.4. Mobility in soil

| Hazardous components | LogPow | Bioconcentration | Exposure | Species | Temperature | Method |
|---------------------------------------|---------|------------------|----------|-------------|-------------|----------------------------|
| CAS-No. | | factor (BCF) | time | | | |
| Isothiazolinone mixture 3:1 (CIT/MIT) | | 3,6 | | calculation | | not specified |
| 55965-84-9 | | | | | | |
| Isothiazolinone mixture 3:1 | -0,71 - | | | | 20 °C | OECD Guideline 117 |
| (CIT/MIT) | 0,75 | | | | | (Partition Coefficient (n- |
| 55965-84-9 | | | | | | octanol / water), HPLC |
| | | | | | | Method) |

12.5. Results of PBT and vPvB assessment

| Hazardous components | PBT/vPvB |
|---------------------------------------|--|
| CAS-No. | |
| Isothiazolinone mixture 3:1 (CIT/MIT) | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very |
| 55965-84-9 | Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.



MSDS-No.: 278985 blaugelb Acryl Dichtmasse all Colours Page 8 of 9

V001.9

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 0,00 %

(VOCV 814.018 VOC regulation

CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: 2, water-endangering product. (German VwVwS of May 17, 1999)

Classification in conformity with the calculation method

Storage class according to TRGS 510: 10



MSDS-No.: 278985 blaugelb Acryl Dichtmasse all Colours Page 9 of 9

V001.9

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H301 Toxic if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Label elements (DPD):

Safety phrases:

S2 Keep out of the reach of children.

Additional information:

The product is not subject to classification according to the calculation methods of the "General Classification Guideline for Preparations of the EC" as issued in the last version.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.