

Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 11

SDS No.: 278987 V003.2

Revision: 04.05.2017 printing date: 04.05.2017 Replaces version from:

10.02.2017

blaugelb Silikon Alkoxy UniPLUS all Colours

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

blaugelb Silikon Alkoxy UniPLUS all Colours

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Joint sealant, silicone

1.3. Details of the supplier of the safety data sheet

Meesenburg Großhandel KG

Westerallee 162

24941 Flensburg / DEUTSCHLAND

Phone: +49 (0)461 5808-0 Fax-no.: +49 (0)461 5808-1101

E-Mail: Zuständig für das Sicherheitsdatenblatt: sdb@chemiebuero.de

1.4. Emergency telephone number

Beratungsstelle +49 (0)89-19240 (24h) (deutsch und englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information Contains 3-Aminopropyltriethoxysilane. May produce an allergic reaction.

Precautionary statement: P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area.

2.3. Other hazards

Evolves methanol during cure.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.



blaugelb Silikon Alkoxy UniPLUS all Colours

MSDS-No.: 278987 V003.2

Page 2 of 11

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

1-Component silicone joint sealant

Base substances of preparation:

Polydimethyl siloxane

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-Reg No. | content | Classification |
|--|-------------------------------|-----------|---|
| Trimethoxyvinylsilane 2768-02-7 | 220-449-8 01-2119513215-52 | 1- < 3 % | Flam. Liq. 3 H226 Acute Tox. 4; Inhalation H332 |
| 3-Aminopropyltriethoxysilane 919-30-2 | 213-048-4 01-2119480479-24 | 0,1-< 1 % | Skin Sens. 1 H317 Skin Corr. 1B H314 Acute Tox. 4; Oral H302 |

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures



MSDS-No.: 278987 blaugelb Silikon Alkoxy UniPLUS all Colours

V003.2

Page 3 of 11

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure that workrooms are adequately ventilated.

Avoid skin and eye contact.

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly sealed.

Store in a cool, dry place.

Temperatures between + 5 °C and + 25 °C

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Joint sealant, silicone



SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for Germany

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|-----------------------------------|-----|-------------------|--|---|-----------------|
| Methanol 67-56-1 [METHANOL] | 200 | 260 | Time Weighted Average (TWA): | Indicative | ECTLV |
| Methanol 67-56-1 | | | Skin designation: | Can be absorbed through the skin. | TRGS 900 |
| Methanol 67-56-1 | 200 | 270 | Exposure limit(s): | If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7). | TRGS 900 |
| Methanol 67-56-1 | | | Short Term Exposure Classification: | Category II: substances with a resorptive effect. | TRGS 900 |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Environmental Exposure Compartment period | | | | Remarks | |
|--|------------------------------------|--|------------|-----|----------------|---------|--|
| | | 1 | mg/l | ppm | mg/kg | others | |
| Trimethoxyvinylsilane 2768-02-7 | aqua (freshwater) | | 0,36 mg/l | | | | |
| Trimethoxyvinylsilane 2768-02-7 | aqua (marine water) | | 0,036 mg/l | | | | |
| Trimethoxyvinylsilane 2768-02-7 | aqua (intermittent releases) | | 2,4 mg/l | | | | |
| Trimethoxyvinylsilane 2768-02-7 | sewage treatment plant (STP) | | 6,6 mg/l | | | | |
| Trimethoxyvinylsilane 2768-02-7 | sediment (freshwater) | | | | 1,3 mg/kg | | |
| Trimethoxyvinylsilane 2768-02-7 | sediment (marine water) | | | | 0,13 mg/kg | | |
| Trimethoxyvinylsilane 2768-02-7 | soil | | | | 0,055 mg/kg | | |
| 3-Aminopropyltriethoxysilane 919-30-2 | aqua (freshwater) | | 0,33 mg/l | | | | |
| 3-Aminopropyltriethoxysilane 919-30-2 | aqua (marine water) | | 0,033 mg/l | | | | |
| 3-Aminopropyltriethoxysilane 919-30-2 | aqua (intermittent releases) | | 3,3 mg/l | | | | |
| 3-Aminopropyltriethoxysilane 919-30-2 | soil | | | | 0,05 mg/kg | | |
| 3-Aminopropyltriethoxysilane 919-30-2 | sewage treatment plant (STP) | | 13 mg/l | | | | |
| 3-Aminopropyltriethoxysilane 919-30-2 | sediment (freshwater) | | | | 1,2 mg/kg | | |
| 3-Aminopropyltriethoxysilane 919-30-2 | sediment (marine water) | | | | 0,12 mg/kg | | |

MSDS-No.: 278987

V003.2

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|--|---------------------|----------------------|--|------------------|------------|---------|
| Trimethoxyvinylsilane 2768-02-7 | Workers | dermal | Long term exposure - systemic effects | | 0,2 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | Workers | Inhalation | Long term exposure - systemic effects | | 2,6 mg/m3 | |
| Trimethoxyvinylsilane 2768-02-7 | General population | dermal | Acute/short term exposure - systemic effects | | 0,1 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | General population | Inhalation | Acute/short term exposure - systemic effects | | 0,7 mg/m3 | |
| Trimethoxyvinylsilane 2768-02-7 | General population | dermal | Long term exposure - systemic effects | | 0,1 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | General population | Inhalation | Long term exposure - systemic effects | | 0,7 mg/m3 | |
| Trimethoxyvinylsilane 2768-02-7 | General population | oral | Long term exposure - systemic effects | | 0,1 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | Workers | dermal | Acute/short term exposure - systemic effects | | 0,2 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | Workers | Inhalation | Acute/short term exposure - systemic effects | | 2,6 mg/m3 | |
| 3-Aminopropyltriethoxysilane 919-30-2 | Workers | dermal | Acute/short term exposure - systemic effects | | 8,3 mg/kg | |
| 3-Aminopropyltriethoxysilane 919-30-2 | Workers | Inhalation | Acute/short term exposure - systemic effects | | 59 mg/m3 | |
| 3-Aminopropyltriethoxysilane 919-30-2 | Workers | dermal | Long term exposure - systemic effects | | 8,3 mg/kg | |
| 3-Aminopropyltriethoxysilane 919-30-2 | Workers | Inhalation | Long term exposure - systemic effects | | 59 mg/m3 | |
| 3-Aminopropyltriethoxysilane 919-30-2 | General population | oral | Acute/short term exposure - systemic effects | | 5 mg/kg | |
| 3-Aminopropyltriethoxysilane 919-30-2 | General population | dermal | Acute/short term exposure - systemic effects | | 5 mg/kg | |
| 3-Aminopropyltriethoxysilane 919-30-2 | General population | Inhalation | Acute/short term exposure - systemic effects | | 17,4 mg/m3 | |
| 3-Aminopropyltriethoxysilane 919-30-2 | General population | oral | Long term exposure - systemic effects | | 5 mg/kg | |
| 3-Aminopropyltriethoxysilane 919-30-2 | General population | dermal | Long term exposure - systemic effects | | 5 mg/kg | |
| 3-Aminopropyltriethoxysilane 919-30-2 | General population | Inhalation | Long term exposure - systemic effects | | 17 mg/m3 | |

Biological Exposure Indices:

None

8.2. Exposure controls:



Page 6 of 11

blaugelb Silikon Alkoxy UniPLUS all Colours

V003.2

MSDS-No.: 278987

Respiratory protection:

The product should only be used at workplaces with intensive ventilation/extraction. If intensive ventilation/extraction is not possible then self-contained independent respiratory protection should be worn.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection:

Goggles which can be tightly sealed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid

pasty

varied, according to

coloration

Odor typical

Odour threshold No data available / Not applicable

pH No data available / Not applicable
Initial boiling point No data available / Not applicable
Flash point No data available / Not applicable
Decomposition temperature No data available / Not applicable
Vapour pressure No data available / Not applicable

Density 1,01 g/cm3

(20 °C (68 °F))

Bulk density

No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

No data available / Not applicable
Explosive properties

No data available / Not applicable

Solubility (qualitative) Insoluble

(23 °C (73.4 °F); Solvent: Water)

Solidification temperature No data available / Not applicable No data available / Not applicable Melting point Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable No data available / Not applicable Explosive limits No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate Vapor density No data available / Not applicable No data available / Not applicable Oxidising properties

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.



10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

Evolves methanol during cure.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Sensitizing:

An allergic reaction cannot be excluded after repeated skin contact.

Acute oral toxicity:

| Hazardous components | Value | Value | Route of | Exposure | Species | Method |
|--------------------------|-------|-------------|-------------|----------|---------|---------------------------|
| CAS-No. | type | | application | time | | |
| Trimethoxyvinylsilane | LD50 | 7.120 mg/kg | oral | | rat | OECD Guideline 401 (Acute |
| 2768-02-7 | | | | | | Oral Toxicity) |
| 3- | LD50 | 1.457 mg/kg | oral | | rat | OECD Guideline 401 (Acute |
| Aminopropyltriethoxysila | | | | | | Oral Toxicity) |
| ne | | | | | | |
| 919-30-2 | | | | | | |

Acute inhalative toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|------------------------------|---------------|-----------|----------------------|---------------|---------|---------------------------|
| Trimethoxyvinylsilane | LC50 | 16,8 mg/l | Vapor. | 4 h | rat | OECD Guideline 403 (Acute |
| 2768-02-7 | | _ | | | | Inhalation Toxicity) |

Acute dermal toxicity:

| Hazardous components | Value | Value | Route of | Exposure | Species | Method |
|--------------------------|-------|-------------|-------------|----------|---------|---------------------------|
| CAS-No. | type | | application | time | | |
| Trimethoxyvinylsilane | LD50 | 3.540 mg/kg | dermal | | rabbit | not specified |
| 2768-02-7 | | | | | | - |
| 3- | LD50 | 4.076 mg/kg | dermal | | rabbit | OECD Guideline 402 (Acute |
| Aminopropyltriethoxysila | | | | | | Dermal Toxicity) |
| ne | | | | | | |
| 919-30-2 | | | | | | |

Skin corrosion/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|--------------------------------|-----------|---------------|---------|-------------|
| 3- Aminopropyltriethoxysila | corrosive | 4 h | rabbit | Draize Test |
| ne 919-30-2 | | | | |

Serious eye damage/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|--------------------------------|-------------------|---------------|---------|---------------|
| 3- Aminopropyltriethoxysila | highly irritating | | rabbit | not specified |
| ne 919-30-2 | | | | |



Respiratory or skin sensitization:

| Hazardous components CAS-No. | Result | Test type | Species | Method |
|--|-------------|-----------------|------------|--|
| 3- Aminopropyltriethoxysila ne 919-30-2 | sensitising | Buehler test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |

SECTION 12: Ecological information

General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following. Do not empty into drains, soil or bodies of water.

12.1. Toxicity

| Hazardous components CAS-No. | Value type | Value | Acute Toxicity Study | Exposure time | Species | Method |
|---------------------------------------|---------------|--------------|----------------------------|---------------|------------------------------|---------------------|
| Trimethoxyvinylsilane | LC50 | 191 mg/l | Fish | 96 h | Oncorhynchus mykiss | OECD Guideline |
| 2768-02-7 | | • | | | | 203 (Fish, Acute |
| | | | | | | Toxicity Test) |
| Trimethoxyvinylsilane | EC50 | > 100 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline |
| 2768-02-7 | | | | | | 202 (Daphnia sp. |
| | | | | | | Acute |
| | | | | | | Immobilisation |
| | | | | | | Test) |
| Trimethoxyvinylsilane | EC50 | > 100 mg/l | Algae | 72 h | | OECD Guideline |
| 2768-02-7 | | | | | | 201 (Alga, Growth |
| | | | | | | Inhibition Test) |
| Trimethoxyvinylsilane | EC 50 | > 2.500 mg/l | Bacteria | 3 h | | OECD Guideline |
| 2768-02-7 | | | | | | 209 (Activated |
| | | | | | | Sludge, Respiration |
| | | | | | | Inhibition Test) |
| 3-Aminopropyltriethoxysilane | LC50 | > 934 mg/l | Fish | 96 h | Brachydanio rerio (new name: | OECD Guideline |
| 919-30-2 | | | | | Danio rerio) | 203 (Fish, Acute |
| | | | | | | Toxicity Test) |
| 3-Aminopropyltriethoxysilane | EC50 | 331 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline |
| 919-30-2 | | | | | | 202 (Daphnia sp. |
| | | | | | | Acute |
| | | | | | | Immobilisation |
| | D050 | -00 4 | | | | Test) |
| 3-Aminopropyltriethoxysilane | EC50 | 603 mg/l | Algae | 72 h | Scenedesmus subspicatus (new | OECD Guideline |
| 919-30-2 | | | | | name: Desmodesmus | 201 (Alga, Growth |
| | MODE | 1.2 // | | 72.1 | subspicatus) | Inhibition Test) |
| | NOEC | 1,3 mg/l | Algae | 72 h | Scenedesmus subspicatus (new | OECD Guideline |
| | | | | | name: Desmodesmus | 201 (Alga, Growth |
| 2 4 . 14 . 1 | EC10 | 12 // | D | - 1 | subspicatus) | Inhibition Test) |
| 3-Aminopropyltriethoxysilane 919-30-2 | EC10 | 13 mg/l | Bacteria | 5 h | | not specified |

12.2. Persistence and degradability

| Hazardous components | Result | Route of | Degradability | Method |
|----------------------|--------|-------------|---------------|--------|
| CAS-No. | | application | | |



MSDS-No.: 278987 blaugelb Silikon Alkoxy UniPLUS all Colours Page 9 of 11

V003.2

| 3-Aminopropyltriethoxysilane | aerobic | 67 % | OECD Guideline 301 A (new |
|------------------------------|---------|------|-----------------------------------|
| 919-30-2 | | | version) (Ready Biodegradability: |
| | | | DOC Die Away Test) |

12.3. Bioaccumulative potential / 12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

| Hazardous components CAS-No. | PBT/vPvB |
|--|---|
| Trimethoxyvinylsilane 2768-02-7 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 3-Aminopropyltriethoxysilane 919-30-2 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.



MSDS-No.: 278987 blaugelb Silikon Alkoxy UniPLUS all Colours

V003.2

Page 10 of 11

14.1. **UN** number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. **Environmental hazards**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 0,00 %

(VOCV 814.018 VOC regulation

CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: 1, slightly water-endangering product. (German VwVwS of May 17, 1999)

Classification in conformity with the calculation method

Storage class according to TRGS 510: 10



blaugelb Silikon Alkoxy UniPLUS all Colours

V003.2

MSDS-No.: 278987

Page 11 of 11

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Label elements (DPD):

Safety phrases:

S2 Keep out of the reach of children.

S24 Avoid contact with skin.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

Additional information:

The product is not subject to classification according to the calculation methods of the "General Classification Guideline for Preparations of the EC" as issued in the last version.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.