



The specialist for cleanliness and protection.

blaugelb Cleaner Alu-ELP

The special cleaner for anodised and powder-coated aluminium surfaces.

Product features:

The blaugelb Cleaner Alu-ELP thoroughly and gently cleans profile surfaces made from anodised and powder-coated aluminium. In window and door construction, it is used for general final cleaning and removal of marking aids.

The blaugelb Cleaner Alu-ELP removes rubber marks, lime and plaster, adhesive residue, fresh PU foam, bitumen and freshly applied silicone sealant – ideal for use in the production and assembly area.

Thanks to its special additives with the ELP system, surfaces are protected against weathering and rapid repeat soiling.

Continued on
the next page ►

- Thorough cleaning
- For the production and assembly area
- Specially suited for anodised and powder-coated surfaces
- ELP additive system for special protection of the surface
- Free of aromatic compounds

blaugelb Cleaner Alu-ELP

The special cleaner for anodised and powder-coated aluminium surfaces.



Technical data:

Basis:	Aliphatic olefin mixture, free of aromatic components, with ELP additive
Colour:	Colourless, clear
Consistency:	Liquid
Density:	Approx. 0.80 g/cm ³
Processing temperature:	Optimally at +5 °C to +25 °C
Hazard class:	A I acc. to VbF (German regulation concerning inflammable liquids)

Product name	PU	Item no.
blaugelb Cleaner Alu-ELP	1,000 ml	0008432
blaugelb Cleaner Alu-ELP	30 l	0008431

Preparation and processing:

Apply the blaugelb Cleaner Alu-ELP to the surfaces to be treated, using a dry, absorbent cloth made from cotton, wool or cellulose.

Before application, the suitability of the material for the intended application is to be verified through appropriate tests performed by the customer. Ensure good ventilation of the work area during and after use and avoid contact with the skin.

Delivery and storage form:

The blaugelb Cleaner Alu-ELP is supplied in a 1,000 ml bottle and in a 30 l canister. If stored in the tightly sealed original container in a dry, well ventilated place, the shelf life is 24 months. Protect against heat and solar radiation.

Disposal:

The disposal conforms with the national specifications.

Safety note:

Please note the safety data sheets. Only for trade use.