

The blaugelb FLK Sealing System – specifically for sealing elements near the ground.



blaugelb FLK Primer PVC Hard

The connection of the blaugelb FLK Sealing System to rigid PVC elements.

- **1C product, ready for use**
- **Fast curing**
- **Adhesive agent specifically for blaugelb FLK Liquid and blaugelb FLK Liquid Corner**
- **Very efficient**
- **Easily dosed**

Product features:

The blaugelb FLK Primer PVC Hard is based on an acrylate dispersion and serves as an adhesive agent for substrates made of rigid PVC (e.g. plastic window frames) with the blaugelb FLK Sealing System. Only for use in combination with blaugelb FLK Liquid and blaugelb FLK Liquid Corner.

The blaugelb FLK Primer PVC Hard can be quickly and easily applied. Safe adhesion to elements made of rigid PVC such as window frame profiles can thus be established.

The blaugelb FLK Primer PVC Hard can also be used on substrates that are equipped with PVC laminated film (e.g. Renolit, Hornschuch).

Product benefits:

- 1C product, ready for use
- Fast curing
- Adhesive agent specifically for blaugelb FLK Liquid and blaugelb FLK Liquid Corner
- Very efficient
- Easily dosed

Technical data:

Processing temperature: (substrate and surroundings)	+10 °C to +30 °C
Substrates:	Rigid PVC, also for PVC laminated film (e.g. Renolit, Hornschuch)
Material consumption:	Approx. 0.20 kg/m ² on a flat, smooth surface
Can be coated over after:	Approx. 40 minutes at 20 °C
Colour:	Grey

Product name	PU	Item no.
blaugelb FLK Primer PVC Hard	0.6 kg plastic can	9143745

Preparation and processing:

The special formula establishes particularly good adhesion and dries quickly. The surface must be clean, dry and free of grease/oil, dust and loose parts. Unstable layers are to be removed. Do not grind the substrate.

The temperature of the substrate should be **at least +10 °C**.

Cover adjacent areas to avoid interactions.

No foreign substances can be added to the blaugelb FLK Sealing System.

Protect blaugelb FLK Primer PVC Hard against solar radiation during storage, transport and use – **even at the construction site**.

Stir the blaugelb FLK Primer PVC Hard thoroughly and apply with a brush.

Allow to dry completely before processing further (approx. 40 minutes at 20 °C). The material layer of the blaugelb FLK Liquid or blaugelb FLK Liquid Corner can then be applied.

For the individual processing steps, please refer to the detailed installation instructions for the blaugelb FLK Sealing System. This can be downloaded on the product page at www.das-neue-blaugelb.de. The processing must exactly follow the specification of the installation instructions.

Delivery and storage form:

Store in its original packaging, unmixed, cool and dry. Shelf life unopened approx. 6 months from production at storage temperature between +10 °C and +30 °C. Protect the can from mechanical damage, sunlight, frost and heat.

Disposal:

The disposal conforms with the national and local specifications. For further information, see the Safety Data Sheet.

Safety note:

Protect the product from mechanical damage, frost, heat and sunlight. Use personal protective equipment (gloves in accordance with EN ISO 374 and tightly sealed goggles). Sufficient ventilation must be ensured during and after processing. Note the Safety Data Sheet. Only for trade use. Perform adequate pretests on compatibility and effect.