

The blaugelb FLK Sealing System – specifically for sealing elements near the ground.



## blaugelb FLK Primer Spezial

The adhesive agent for special substrates in the blaugelb FLK Sealing System.

- **1C product, ready for use, very good processability**
- **Adhesive agent specifically for blaugelb FLK Liquid and blaugelb FLK Liquid Corner on problematic substrates**
- **Small amount required, very efficient**
- **Easily dosed**
- **Rapid further processing**
- **Part of the blaugelb FLK Sealing System**

# blaugelb FLK Primer Special

The adhesive agent for special substrates in the blaugelb FLK Sealing System.



## Product features:

The blaugelb FLK Primer Special is an adhesive agent for difficult substrates such as various plastics (FPO, TPO, EVA) and rubber (EPDM) with the blaugelb FLK Sealing System. Only for use in combination with blaugelb FLK Liquid and blaugelb FLK Liquid Corner.

Thanks to its rapid drying, the blaugelb FLK Primer Special can be coated over quickly.

Thanks to its liquid form, the blaugelb FLK Primer Special can be applied with a brush or roller and can be quickly and easily spread. A reliable substrate adhesion is thus achieved.

**Not suitable for substrates made of bitumen.**

## Product benefits:

- 1C product, ready for use, very good processability
- Adhesive agent specifically for blaugelb FLK Liquid and blaugelb FLK Liquid Corner on problematic substrates
- Small amount required, very efficient
- Easily dosed
- Rapid further processing
- Part of the blaugelb FLK Sealing System
- Suitable for various plastic and rubber surfaces\*

\* See "Substrate preparation" list, carry out suitable pretests

## Technical data:

Processing temperature: (substrate and surroundings)	+5 °C to +35 °C
Substrates:	EPDM, FPO, TPO, EVA Note: Not suitable for bitumen
Material consumption:	Approx. 40 – 80 ml/m <sup>2</sup>
Can be coated over after:	Approx. 20 minutes at 20 °C
Rainproof after:	Approx. 20 minutes at 20 °C
Colour:	Yellowish

Product name	PU	Item no.
blaugelb FLK Primer Special for EPDM FPO TPO EVA	0.5 l metal bottle	9143713

## Preparation and processing:

The special formula establishes particularly good adhesion and dries quickly. The blaugelb FLK Primer Special has been tested with various substrates which are considered difficult when it comes to establishing adhesion (see also the separate "Substrate preparation" list on the product page at [www.das-neue-blaugelb.de](http://www.das-neue-blaugelb.de)). **Not suitable for bitumen.**

The surface must be clean, dry and free of grease/oil, dust and loose parts. Unstable layers are to be removed.

The compatibility and adhesion with the substrate and adjacent materials must be checked before the respective application in each case by the processor based on the variety of structural conditions. Cover adjacent areas

to avoid interactions as the blaugelb FLK Primer Special contains solvents.

No foreign substances can be added to the blaugelb FLK Sealing System.

The temperature of the substrate surface must be at least 3 °C higher than the dew point so that the formation of a separating layer (moisture film) is prevented (see DIN 4108, "Dew point temperature table").

Protect the blaugelb FLK Primer Special against solar radiation during storage, transport and use – **even at the construction site.**

Apply the blaugelb FLK Primer Special with a roller or brush and allow to dry completely before processing further (approx. 20 minutes at 20 °C).

For the individual processing steps, please refer to the detailed installation instructions for the blaugelb FLK Sealing System. This can be downloaded on the product page at [www.das-neue-blaugelb.de](http://www.das-neue-blaugelb.de).

## Delivery and storage form:

Store in its original packaging, unmixed, cool, free of frost and dry. Shelf life unopened approx. 6 months from production at storage temperature between +5 °C and +20 °C. Protect the can from mechanical damage, sunlight, frost and heat.

## Disposal:

The disposal conforms with the national and local specifications. For further information, see the Safety Data Sheet.

## Safety note:

Protect the product from mechanical damage, heat and sunlight. Use personal protective equipment (gloves in accordance with EN ISO 374 and tightly sealed goggles). Sufficient ventilation must be ensured during and after processing. Note the Safety Data Sheet. Only for trade use. Perform adequate pretests on compatibility and effect.

The information provided in this document corresponds to the information and technical details available to the best of our knowledge. However, this does not constitute a guarantee pursuant to section 443 of the German Civil Code (BGB). Our processing instructions are to be considered only as general guidelines and may differ in the individual case due to the range of possible uses and applications. They do not therefore automatically exempt the user from carrying out their own tests. We reserve the right to make technical modifications and enhancements at any time.