

The blaugelb FLK Sealing System – specifically for sealing elements near the ground.



blaugelb FLK Quartz Sand

The safe adhesive primer in the blaugelb FLK Sealing System for subsequent work.

- **Ready for use, very simple processability**
- **Application possible by hand or with a suitable gun**
- **Selected grain size**
- **High quality**

Product features:

The blaugelb FLK Quartz Sand is a high-quality spreading material for sanding surfaces that are sealed with blaugelb FLK Liquid and blaugelb FLK Liquid Corner.

The blaugelb FLK Quartz Sand is used so that subsequent work can be attached to the created seal without any trouble. These encounter an ideal adhesive primer for additional coatings. The coatings can “sink their claws” into the rough surface structure of the blaugelb FLK Quartz Sand and thus establish good adhesion and impermeability.

Sanding is thus the last step in the sequence of work steps: Attachment to the existing building waterproofing – sealing of the connecting joint – preparation for subsequent work. The construction site is left in the ideal condition and smooth further processing is enabled.

Product benefits:

- Ready for use, very simple processability
- Application possible by hand or with a suitable gun
- Selected grain size
- High quality

Technical data:

Material:	Quartz sand
Grain size:	0.71 – 1.25 mm
Colour:	Beige

Product name	PU	Item no.
blaugelb FLK Quartz Sand 25 kg	25 kg bag	9143749

Preparation and processing:

Sand application is performed directly on the fresh surface layer of the blaugelb FLK Liquid or blaugelb FLK Liquid Corner. The blaugelb FLK Quartz Sand can be thrown in by hand or applied with a suitable quartz sand gun.

Excess quartz sand can **be carefully brushed off after 24 hours.**

For the individual processing steps, please refer to the detailed installation instructions for the blaugelb FLK Sealing System. This can be downloaded on the product page at www.blaugelb.de. The processing always complies with the specification of the installation instructions.

The compatibility and adhesion with the substrate and adjacent materials must be checked before the respective application in each case by the processor based on the variety of structural conditions. No foreign substances can be added to the blaugelb FLK Liquid.

Cleaning and repair:

Cleaning with blaugelb Cleaner PVC-S10 UVA is possible before curing; after curing the blaugelb FLK Liquid and blaugelb FLK Liquid Corner can only be removed mechanically. The quartz sand layer can be removed by grinding down if this is necessary.

If the surface layer is sanded, a new coat of the blaugelb FLK Liquid or blaugelb FLK Liquid Corner can be applied without primer or grinding down. The sanded layer must be roughly cleaned beforehand, e.g. with a moist broom.

Delivery and storage form:

Store in its original packaging, cool and dry. Protect from sunlight, moisture, frost and heat. Shelf life unopened unlimited at storage temperatures between +5 °C and +35 °C. Protect opened containers from humidity, reseal immediately. Do not mix with other materials.

Disposal:

The disposal conforms with the national and local specifications.

Safety note:

The product is not classified as hazardous according to the regulation (EC) No. 1272/2008 (CLP). Only for trade use. Perform adequate pretests on compatibility and effect.